

Each Series of linear guideway with different dust-proof accessories, comparing with standard dust-proof accessories, the overall length of carriage is different, as below table shown:

### MSA Series

Unit: mm

Model No.	No symbol	UU	SS	LL	RR	ZZ	DD	KK	HD
15	1	-	-	-	-	6	5	11	3
20	1.4	-	-	-	-	7	5.6	12.6	0.4
25	1.4	-	-	-	-	7	5.6	12.6	0.4
30	1.4	-	-	-	-	7	5.6	12.6	0.4
35	0.6	-	-	-	-	7.8	7.2	15	-
45	0.6	-	-	-	-	7.8	7.2	15	-
55	-	-	-	-	-	7.8	7.8	15.6	-
65	-	-	-	-	-	7.8	7.8	15.6	-

### MSB Series

Unit: mm

Model No.	No symbol	UU	SS	LL	RR	ZZ	DD	KK	HD
15	-	-	-	-	-	5	5	10	1
20	1	-	-	-	-	7	6	13	-
25	1	-	-	-	-	7	6	13	-
30	1	-	-	-	-	7	6	13	-
35	0.6	-	-	-	-	7.8	7.2	15	-
45	0.6	-	-	-	-	7.8	7.2	15	-

**MSG Series**

Unit: mm

Model No.	no symbol	UU	SS	ZZ	DD	KK
17	-	-	-	6	6	12
21	-	-	-	6	6	12
27	1	-	-	7	6	13
35	1.8	-	-	7.8	6	13.8

**MSR, SMR Series**

Unit: mm

Model No.	no symbol	UU	SS	ZZ	DD	KK
MSR 20	-	-	-	6	6	12
MSR 25	SMR 25	-	-	6	6	12
MSR 30	SMR 30	1	-	7	6	13
MSR 35	SMR 35	1	-	7	6	13
MSR 45	SMR 45	0.6	-	7	6.4	13.4
MSR 55	SMR 55	0.6	-	7.8	7.2	15
MSR 65	SMR 65	-0.2	-	7.8	8	15.8

**SME Series**

Unit: mm

Model No.	no symbol	UU	SS	ZZ	DD	KK
15	1.6	-	-	7	5.4	12.4
20	1	-	-	7	6	13
25	1	-	-	7	6	13
30	1	-	-	7	6	13
35	1	-	-	7.8	6.8	14.6
45	0.6	-	-	7.8	7.2	15